

RECEIVED
CENTRAL FAX CENTER

OCT 31 2007

AMENDMENTS TO THE CLAIMS:

This listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims:

Claim 1 (Cancelled)

2. (Currently Amended) A damper assembly with a torque limiter, said damper assembly having a single torque transmission path between an input axis and an output axis, and comprising:

a friction torque limiter between said input axis or said output axis and an airtight damper, said friction torque limiter being in series with said damper and limiting the torque which can be transmitted through said damper, wherein said friction torque limiter is disposed outside said airtight damper and includes a torque transmission plate fixed to a drive member of the damper, and a friction plate held in frictional engagement with said torque transmission plate by a press plate having a radially ~~outer~~ outermost peripheral portion spline engaged with a radially inner peripheral portion of a torque transmitting member and pressed toward said torque transmission plate by a press spring.

Claims 3-4 (Cancelled)

5. (Currently Amended) A damper assembly with a torque limiter, said damper assembly having a single torque transmission path between an input axis and an output axis, and comprising:

a friction torque limiter between said input axis or said output axis and an airtight damper, said friction torque limiter being in series with said damper and limiting the torque which can be transmitted through said damper, wherein said friction torque limiter is provided inside said airtight damper and includes a ring member having opposite axial end portions and a circumferential sidewall portion joining said opposite axial end portions, said circumferential sidewall portion having a conical periphery coaxial with a rotation axis of the damper assembly and providing a friction surface through which torque is transmitted in said friction path.

6. (Previously Presented) A damper assembly with a torque limiter according to Claim 5, wherein said friction surface is a radially outer peripheral surface of said circumferential sidewall portion of said ring member.

7. (Currently Amended) A damper assembly with a torque limiter, said damper assembly having a single torque transmission path between an input axis and an output axis, and comprising:

a friction torque limiter between said input axis or said output axis and an airtight damper, said friction torque limiter being in series with said damper and limiting the torque which can be transmitted through said damper, wherein said friction torque limiter is provided inside said airtight damper and includes a ring member having opposite axial end portions and a circumferential sidewall portion joining said opposite axial end portions, said circumferential sidewall portion having a conical peripheral friction surface which is coaxial with a rotation axis of the damper assembly and frictionally engaged with an adjacent conical surface and through which torque is thereby transmitted in said friction path.

8. (Previously Presented) A damper assembly with a torque limiter according to Claim 7, wherein said friction surface is a radially outer peripheral surface of said circumferential sidewall portion of said ring member.

9. (Currently Amended) A damper assembly with a torque limiter, said damper assembly having a single torque transmission path between an input axis and an output axis, and comprising:

a friction torque limiter between said input axis or said output axis and an airtight damper, said friction torque limiter being in series with said damper ~~and limiting the torque which can be transmitted through said damper,~~ wherein said torque limiter is provided inside said airtight damper and includes a plurality of ~~wet~~ friction plates provided with wet-type friction material which limits the torque that can be transmitted through said damper.

10. (Currently Amended) A damper assembly with a torque limiter according to Claim 9, wherein said ~~wet~~ friction plates are pressed by a spring.

11. (Currently Amended) A damper assembly with a torque limiter according to Claim 10, wherein adjacent ~~wet~~ friction plates are arranged with a torque transmission plate disposed therebetween.

12. (Currently Amended) A damper assembly with a torque limiter according to Claim 11, wherein said ~~wet~~ friction plates are spline engaged with one of a torque transmitting member and a drive plate of said airtight damper, and said torque transmission plate is spline engaged with the other of said torque transmitting member and said drive plate.

13. (Currently Amended) A damper assembly with a torque limiter according to Claim 11, wherein said ~~wet~~ friction plates are spline engaged with a radially adjacent member.